

# maratodd

## L I G H T I N G

### FIXTURE TYPE

## M A R I A N N E

155 West 3rd St • New Richmond, WI 54017  
p: 715.246.2233 f: 715.246.2243  
www.maratodd.com



## M A R I A N N E

|             |             |
|-------------|-------------|
| DATE        |             |
| ITEM #      | MT-MARIANNE |
| PROJECT     |             |
| COMMENTS    |             |
| PREPARED BY |             |

## D E S C R I P T I O N

Double Tier Drum Pendant Light

## S P E C I F I C A T I O N F E A T U R E S

### MATERIAL / MOUNTING

Cold-rolled steel frame wire body.  
Matte white acrylic bottom diffuser (Optional).

### SHADES

Solid cold-rolled steel construction.  
Material on heavy translucent white styrene with your choice of the coverings opacity.

### FINISH

Standard: White (WHI)  
Premium: Nickel (NIC), Brass (BRA),  
Black (BLA), Ivory (IVO), Oil-Rubbed  
Bronze (ORB)

### ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

### LIGHTING

5-way, standard socket cluster. Works with incandescent or LED bulbs.

### INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box.  
120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

## ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.  
Pre-selected values may also be modified, if required.

## MARIANNE

### SERIES

MARIANNE: Double Tier Drum  
Pendant Light

| 20   |  | 4.5  |  | SRS   |  |  |  |
|--|--|--|--|---|--|--|--|
| <u>OUTER SHADE DIAMETER</u>  |  | <u>OUTER SHADE HEIGHT</u>  |  | <u>CANOPY TYPE</u>  |  | <u>CANOPY COLOR</u>  |  |
| 16   |  | 2  |  | SRS: Swivel Rigid Stem<br>FC: Flex Cord<br>AC: Aircraft Cable with Flex Cord          |  | STANDARD<br>WHI: White<br>PREMIUM<br>NIC: Nickel<br>BRA: Brass<br>BLA: Black<br>IVO: Ivory<br>ORB: Oil-Rubbed Bronze                                       |  |
| <u>INNER SHADE DIAMETER</u>  |  | <u>INNER SHADE EXPOSED HEIGHT</u>  |  |   |  | <u>STEM COLOR</u>  |  |
| IN INCHES<br>6, 8, 10, 12, 14, 16,<br>18, 20, 22, 24, 26,<br>28, 30, 32, 34, 36,<br>38, 40, 42, 44, 46,<br>48, 50, 52, 54, 56,<br>58, 60 |  | IN INCHES<br>6, 8, 10, 12, 14, 16,<br>18, 20, 22, 24, 26,<br>28, 30, 32, 34, 36,<br>38, 40, 42, 44, 46,<br>48, 50, 52, 54, 56,<br>58, 60 |  |   |  | 3/8" Round Steel<br>STANDARD<br>ST-WHI: White<br>PREMIUM<br>ST-NIC: Nickel<br>ST-BRA: Brass<br>ST-BLA: Black<br>ST-IVO: Ivory<br>ST-ORB: Oil-Rubbed Bronze |  |
|  |  |  |  | A   |  | 3  |  |
| <u>LAMP SHADE OPACITY</u>  |  | <u>LAMP SHADE COVERING</u>   |  | <u>ACRYLIC DIFFUSER</u>   |  | <u>HEIGHT FROM CEILING TO SHADE BOTTOM</u>   |  |
| OPAQUE:<br>Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade)              |  | STANDARD<br>(Some Examples)<br>L-CRE: Linen Cream<br>L-WHI: Linen White  |  | A: With Acrylic Diffuser<br>FBD: With Fabric Diffuser<br>NA: Without Acrylic Diffuser |  | Specify the Length<br>6, 8, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, or CUSTOM  |  |
| TRANSLUCENT:<br>Shade covering allows some light to shine through. Vertical bars are exposed.  |  | PREMIUM<br>(Some Examples)<br>DL-OFF: Designer Linen Off-White<br>VC-WHI: Vinyl Coated White   |  |   |  |  |  |
| VERTICAL TRIM:<br>1/2" trim applied to shade exterior over vertical support bars to hide shadows.  |  |  |  |   |  | CUSTOM: Enter Actual Measurement in Inches   |  |
|  |  |  |  |   |  | <u>BULBS</u>   |  |
|  |  |  |  |   |  | Number of Bulbs Depends on Socket<br>9W2700:<br>800 Lumens 2,700K<br>15W2700:<br>1,600 Lumens 2,700K<br>NA: No Bulbs                                       |  |