



RICO

DATE	
ITEM #	MT-RICO
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

Round Tapered Pendant Light

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body.
Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction.
Material on heavy translucent white styrene with your choice of the coverings opacity.

FINISH

Standard: White (WHI)
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

LIGHTING

3-way, standard socket cluster. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.
Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.
Pre-selected values may also be modified, if required.

RICO

S E R I E S

RICO: Round Tapered
Pendant Light

3 2

1 6

S R S

SHADE TOP
DIAMETER

IN INCHES
6, 8, 10, 12, 14, 16,
18, 20, 22, 24, 26

3 6

SHADE BOTTOM
DIAMETER

IN INCHES
6, 8, 10, 12, 14, 16,
18, 20, 22, 24, 26

SHADE
HEIGHT

IN INCHES
6, 8, 10, 12, 14, 16,
18, 20, 22, 24, 26,
28, 30, 32, 34, 36,
38, 40, 42, 44, 46,
48, 50, 52, 54, 56,
58, 60

S U S P E N S I O N
S T Y L E

SRS: Swivel Rigid Stem
FS: Fixed Stem
FC: Flex Cord
AC: Aircraft Cable with
Flex Cord

C A N O P Y
C O L O R

STANDARD
WHI: White
PREMIUM
NIC: Nickel
BRA: Brass
BLA: Black
IVO: Ivory
ORB: Oil-Rubbed Bronze

H E I G H T
F R O M
C I E L I N G
T O S H A D E
B O T T O M

6, 8, 12, 14, 16, 18, 20, 22,
24, 26, 28, 30, 32, 34, 36,
38, 40, 42, 44, 46, 48,
or CUSTOM
CUSTOM: ENTER ACTUAL
MEASUREMENT IN INCHES

A

5

L A M P S H A D E
O P A C I T Y

OPAQUE:
Features an interior
light-blocking layer to
make shade opaque. (No
light passes through the
sides of the shade)
TRANSLUCENT:
Shade covering allows
some light to shine
through.
VERTICAL TRIM:
1/2" trim applied to
shade exterior over
vertical support bars to
hide shadows.

L A M P S H A D E
C O V E R I N G

STANDARD
(Some Examples)
L-CRE: Linen Cream
L-WHI: Linen White
PREMIUM
(Some Examples)
DL-OFF: Designer Linen
Off-White
VC-WHI: Vinyl Coated
White

A C R Y L I C
D I F F U S E R

A: With Acrylic
Diffuser
FBD: With Fabric
Diffuser
NA: Without
Acrylic Diffuser

L A M P I N G

Specify Number of
Light Sockets
1, 2, 3, 5

B U L B S

Number of Bulbs
Depends on Socket
9W2700:
800 Lumens 2,700K
15W2700:
1,600 Lumens 2,700K
NA: No Bulbs