



OTTO

DATE	
ITEM #	MT-OTTO
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

Round Drum Pendant Light

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body.
Matte white acrylic bottom diffuser
(Optional).

SHADES

Solid cold-rolled steel construction.
Material on heavy translucent white
styrene with your choice of the
coverings opacity.

FINISH

Standard: White (WHI)
Premium: Nickel (NIC), Brass (BRA),
Black (BLA), Ivory (IVO), Oil-Rubbed
Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White
with a thickness of 0.118. Custom
colors are available, but may impact
extended lead time and standard price.

LIGHTING

Single Socket. Works with
incandescent or LED bulbs.

INSTALLATION

Easy-to-install. Attaches to standard 4"
junction box. 120V power.
Cleaning Recommendation: Use a soft
cloth brush or a vacuum brush to dust
the outside of the lamp shade and a
clean soft white flannel cloth for the
inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire
Resistant or Stain Guard Fabric
coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with
their depth of experience, offer the
designer the flexibility to modify
standard luminaries for project-specific
solutions. Contact the factory
regarding scale options, unique
finishes, mounting, additional
materials/colors or decorative detail-
ing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.
Pre-selected values may also be modified, if required.

OTTO

S E R I E S

OTTO: Round Drum
Pendant Light

1 1

3 0

F C

S H A D E
D I A M E T E R

IN INCHES

6, 8, 10, 12, 14, 16,
18, 20, 22, 24, 26,
28, 30, 32, 34, 36,
38, 40, 42, 44, 46,
48, 50, 52, 54, 56,
58, 60

S H A D E
H E I G H T

IN INCHES

6, 8, 10, 12, 14, 16,
18, 20, 22, 24, 26,
28, 30, 32, 34, 36,
38, 40, 42, 44, 46,
48, 50, 52, 54, 56,
58, 60

S U S P E N S I O N
S T Y L E

SRS: Swivel Rigid Stem

FS: Fixed Stem

FC: Flex Cord

AC: Aircraft Cable with
Flex Cord

C A N O P Y
C O L O R

STANDARD

WHI: White

PREMIUM

NIC: Nickel

BRA: Brass

BLA: Black

IVO: Ivory

ORB: Oil-Rubbed Bronze

C O R D
C O L O R

C-WHT: WHITE

C-BLK: BLACK

C O R D
L E N G T H

4FEET 12 FEET
8 FEET 16 FEET

A

1

L A M P S H A D E
O P A C I T Y

OPAQUE:

Features an interior
light-blocking layer to
make shade opaque. (No
light passes through the
sides of the shade)

TRANSLUCENT:

Shade covering allows
some light to shine
through.

L A M P S H A D E
C O V E R I N G

STANDARD

(Some Examples)

L-CRE: Linen Cream

L-WHI: Linen White

PREMIUM

(Some Examples)

DL-OFF: Designer Linen
Off-White

VC-WHI: Vinyl Coated
White

A C R Y L I C
D I F F U S E R

A: With Acrylic
Diffuser

FBD: With Fabric
Diffuser

NA: Without
Acrylic Diffuser

L A M P I N G

Specify Number of
Light Sockets

1, 2, 3, 5

B U L B S

Number of Bulbs
Depends on Socket

9W2700:

800 Lumens 2,700K

15W2700:

1,600 Lumens 2,700K

NA: No Bulbs