maratodd

FIXTURE TYPE

EMILIE TAPERED DOUBLE TIER SWIVEL RIGID STEM

www.maratodd.com

EMILIE

DATE	
ITEM#	MT-EMILIE-TAPERED-DOUBLE TIER - SWIVEL RIGID STEM
PROJECT	
COMMENTS	
PREPARED BY	



EMILIE Round Tapered Double Tier Pendant Light with Swivel Rigid Stem Suspension Style.



SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)

Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed

Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

EMILIE TAPERED DOUBLE TIER SWIVEL RIGID STEM

SERIES

EMILIE: Round Tapered Double Tier Pendant Light

25 OUTER SHADE TOP DIAMETER 26 OUTER SHADE BOTTOM DIAMETER 20 INNER SHADE TOP DIAMETER 18 INNER SHADE BOTTOM DIAMETER Even numbers only in	SLANT HEIGHT 7 INNER SHADE EXPOSED HEIGHT Even numbers only in inches, minimum 4" with maximum of 48"	SRS SUSPENSION STYLE SRS: Swivel Rigid Stem	Single Double Triple 5-Bulb	9W 800 Lumer 1,600 Lum 2,400 Lum 4,000 Lum	ens 3,200 Lumens ens 4,800 Lumens
inches, minimum 6" with maximum of 84" DISTANCE FROM CEILING TO INNER SHADE BOTTOM In inches, up to 192"	STEM COLOR 3/8" Round Steel STANDARD ST-WHI: White PREMIUM ST-NIC: Nickel ST-BRA: Brass ST-BLA: Black ST-IVO: Ivory ST-ORB: Oil-Rubbed Bronze CANOPY COLOR STANDARD WHI: White PREMIUM NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bronze	LAMPSHADE OPACITY OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed. VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to hide shadows.	LAMPSI COVEI STAND (Some Ex L-CRE: Lines L-WHI: Lines PREM (Some Ex DL-OFF: De Linen Off-W VC-WHI: Vit White	RING DARD camples) n Cream n White IUM camples) esigner hite	A ACRYLIC DIFFUSER A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser Note: Fixture Diameters of 40"+ get Diffuser Risers and Finials