maratodd

FIXTURE TYPE

HENRIETTE OVAL FLEX CORD

www.maratodd.com

HENRIETTE

DATE	
ITEM #	MT-HENRIETTE-OVAL-FLEX
	CORD
PROJECT	
COMMENTS	
PREPARED BY	
TREFFICED D1	



DESCRIPTION

HENRIETTE Oval Pendant Light with Flex Cord Suspension Style with Optional Aircraft Cable.

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)

Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed

Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

HENRIETTE-OVAL FLEX CORD

<u>SERIES</u>

HENRIETTE: Oval Pendant Light

30 x 15	15	FC	5		
SHADE TOP	SHADE HEIGHT	SUSPENSION	<u>SOCKET</u>	BRIGHTNESS	
<u>DIMENSION</u> Even numbers only in inches, minimum 6"	Numbers only in inches, minimum 4"	STYLE FC: Flex Cord Only AC: Aircraft Cable		<u>9W</u>	<u>15W</u>
with maximum of 84" 30 x 15	with maximum of 40"	Option	Single Double	800 Lumens 1,600 Lumens	1,600 Lumens 3,200 Lumens
SHADE BOTTOM DIMENSION		Note: Optional on fixtures up to 38" in diameter	Triple 5-Bulb	2,400 Lumens 4,000 Lumens	4,800 Lumens 8,000 Lumens
Even numbers only in inches, minimum 6" with maximum of 84"		Required on fixtures with diameter of 40" +		<u>COLOR TEM</u> 2,700K - W 3,000K - S	arm White

				Α
POWER CORD LENGTH In inches, up to 192" POWER CORD COLOR STANDARD C-BLA: Black C-WHI: White	CANOPY COLOR STANDARD WHI: White PREMIUM NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bronze	LAMPSHADE OPACITY OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed. VERTICAL TRIM:	LAMPSHADE COVERING STANDARD (Some Examples) L-CRE: Linen Cream L-WHI: Linen White PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated White	A ACRYLIC DIFFUSER A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser Note: Fixture Diameters of 40"+ get Diffuser Risers and Finials
		1/2" trim applied to		
		shade exterior over vertical support bars to hide shadows.		