# maratodd

#### FIXTURE TYPE

#### RAINA TAPERED DOUBLE TIER SWIVEL RIGID STEM

www.maratodd.com

#### RAINA

DATE	
ITEM#	MT-RAINA-TAPERED-DOUBLE TIER - SWIVEL RIGID STEM
PROJECT	
COMMENTS	
PREPARED BY	

## DESCRIPTION

RAINA Round Tapered Double Tier Pendant Light with Swivel Rigid Stem Suspension Style.



#### SPECIFICATION FEATURES

#### MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

#### **SHADES**

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

#### **FINISH**

Standard: White (WHI)

Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed

Bronze (ORB)

#### ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

#### **LIGHTING**

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

#### **INSTALLATION**

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

#### **OPTIONS**

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

#### **USAGE**

Approved for interior locations only.

#### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

### ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

# CUSTOM TAPERED DOUBLE TIER SWIVEL RIGID STEM

#### <u>SERIES</u>

CUSTOM: Round Tapered Double Tier Pendant Light

23 OUTER SHADE TOP DIAMETER  24 OUTER SHADE BOTTOM DIAMETER  18 INNER SHADE TOP DIAMETER  16 INNER SHADE BOTTOM DIAMETER  Even numbers only in inches, minimum 6" with maximum of 84"	SLANT HEIGHT  5  INNER SHADE EXPOSED HEIGHT Even numbers only in inches, minimum 4" with maximum of 48"	SRS  SUSPENSION  STYLE  SRS: Swivel Rigid Stem	Single Double Triple 5-Bulb	9W 800 Lumer 1,600 Lum 2,400 Lum 4,000 Lum	ens 3,200 Lumens ens 4,800 Lumens ens 8,000 Lumens  OR TEMPERATURE  00K – Warm White  000K – Soft White
DISTANCE FROM CEILING TO INNER SHADE BOTTOM In inches, up to 192"	STEM COLOR  3/8" Round Steel  STANDARD  ST-WHI: White  PREMIUM  ST-NIC: Nickel  ST-BRA: Brass  ST-BLA: Black  ST-IVO: Ivory  ST-ORB: Oil-Rubbed  Bronze  CANOPY COLOR  STANDARD  WHI: White  PREMIUM  NIC: Nickel  BRA: Brass  BLA: Black  IVO: Ivory  ORB: Oil-Rubbed Bronze	OUTER / INNER LAMPSHADE OPACITY  OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed. VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to hide shadows.	OUTER / LAMPSI COVEL STAND (Some Ex L-CRE: Liner L-WHI: Liner PREM (Some Ex DL-OFF: De Linen Off-WI VC-WHI: Vir White	HADE RING DARD amples) in Cream in White IUM amples) signer thite	A  ACRYLIC DIFFUSER  A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser  Note: Fixture Diameters of 40" + get Diffuser Risers and Finials