

# LUMA SHADE

FIXTURE TYPE

**FARGO**

www.maratodd.com

## FARGO

DATE	
ITEM #	LS-FARGO
PROJECT	
COMMENTS	
PREPARED BY	



## DESCRIPTION

Lumashade Custom ROUND Pendant Light

## SPECIFICATION FEATURES

### CONSTRUCTION

1/4" steel wireframe, painted for optimum reflectivity.

Power source located on-board or remote in ceiling.

Cable mount suspension system (supplied).

### LIGHT SOURCE

Proprietary epoxy encased light emitting diode round disc.

### NO. LEDs AND LIGHT OUTPUT

8" Round Disc (87 LEDs) - 1,800 Max Lumens

16" Round Disc (192 LEDs) - 4,000 Max Lumens

24" (440 LEDs) and 32" (446) Round Disc - 9,000 Max Lumens

### COLOR RENDERING INDEX

>75

### MAXIMUM WATTAGE

8" Round Disc - 18.2W

16" Round Disc - 40W

24" and 32" Rounds Disc - 90W

### ENVIRONMENT

Dry or Damp

### AMBIENT TEMPERATURE

22°F - 122°F

### CONTROLLER

MW UL Approved (>20W, >40W or >90W depending on LED disc selected).

### CERTIFICATIONS

CE, RoHS, FCC, IP-67

### INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Lumashade's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

## ORDERING INFORMATION

Please fill in all **blue highlighted** areas for complete specification.  
Pre-selected values in black may also be modified, if required.

<b>FARGO</b>
<b>SERIES</b>
<b>FARGO: Lumashade ROUND Pendant Light</b>

<b>22</b>	<b>12</b>	<b>AC</b>		
-----------	-----------	-----------	--	--

<p><u>TOP DIAMETER</u> Even numbers only in inches, minimum 6" with maximum of 84"</p>	<p><u>SHADE HEIGHT</u> Even numbers only in inches, minimum 4" with maximum of 48"</p>	<p><u>SUSPENSION STYLE</u> AC: Aircraft Cable</p>	<p><u>LUMA DISC SIZE</u> 8.8" Luma Disc 16:16" Luma Disc 24:24" Luma Disc 32:32" Luma Disc</p>	<p><u>COLOR TEMPERATURE</u> 2,700K-3200K: Warm White 3,700K-4200K: Neutral White</p>
<b>22</b>				
<p><u>BOTTOM DIAMETER</u> Even numbers only in inches, minimum 6" with maximum of 84"</p>				<p><u>DIMMING</u> N: No Dimming 0-10W: 0-10V PWM Dimming RC: Remote Control Dimming</p>

				<b>A</b>
--	--	--	--	----------

<p><u>DISTANCE FROM CEILING TO SHADE BOTTOM</u> In inches, up to 192"</p>	<p><u>CANOPY COLOR</u> STANDARD WHI: White PREMIUM NIC: Nickel BRA: Brass BLA: Black IVO: Ivory ORB: Oil-Rubbed Bronze</p>	<p><u>LAMPSHADE OPACITY</u> OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade)  TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed.  VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to hide shadows.</p>	<p><u>LAMPSHADE COVERING</u> STANDARD (Some Examples) L-CRE: Linen Cream L-WHI: Linen White  PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated White</p>	<p><u>DIFFUSER</u> A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser  Note: Fixture Diameters of 40"+ get Diffuser Risers and Finials</p>
<p><u>POWER CORD COLOR</u> STANDARD C-BLA: Black C-WHI: White</p>				