maratodd L I G H T I N G

JAKOB

DATE	
ITEM #	Drum Pendant Light with Swivel Rigid Stem
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

Drum Pendant Light with Swivel Rigid Stem Suspension Style.

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

<u>Shades</u>

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

<u>FINISH</u>

Standard: White (WHI) Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

<u>USAGE</u>

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.





FIXTURE TYPE JAKOB DRUM SWIVEL RIGID STEM www.maratodd.com

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

JAKOB DRUM SWIVEL RIGID STEM

<u>S E R I E S</u>

JAKOB Round Drum Pendant Light

48	14	SRS	5			
		<u>SUSPENSION</u>	<u>SOCKE</u>	T	BRIGHTNESS	
<u>DIAMETER</u> Even numbers only in	Even numbers only in SRS	<u>STYLE</u> S: Swivel Rigid		<u>9W</u>	<u>15W</u>	
inches, minimum 6"	inches, minimum 4" Ste	0	Single	800 Lume		
with maximum of 84"	with maximum of 48"		Double	1,600 Lum	ens 3,200 Lumens	
			Triple	2,400 Lum	ens 4,800 Lumens	
			5-Bulb	4,000 Lum	ens 8,000 Lumens	
				COLO	R TEMPERATURE	
				2,70	0K - Warm White	
				3,00	00K – Soft White	
					А	
DISTANCE FROM	STEM COLOR	LAMPSHAI	DE	LAMPSHADE	DIFFUSER	
<u>CEILING TO INNER</u> <u>SHADE BOTTOM</u>	3/8" Round Steel	<u>OPACITY</u>	<u>Ľ</u>	<u>COVERING</u>		
In inches, up to 192"	STANDARD	OPAQUE	:	STANDARD	A: With Acrylic	
	ST-WHI: White	Features an interior		(Some Examples)	Diffuser FBD: With Fabric	
		light-blocking la	iyer L-	CRE: Linen Cream	Diffuser	
	PREMIUM	to make shade		WHI: Linen White	NA: Without Acrylic	
	ST-NIC: Nickel ST-BRA: Brass	opaque. (No lig passes through			Diffuser	
	ST-BLA: Black			PREMIUM	Note: Fixture	
	ST-IVO: Ivory	sides of the sha		(Some Examples)	Diameters of 40" + get	
	ST-ORB: Oil-Rubbed	TRANSLUCE	D	L-OFF: Designer	Diffuser Risers and	
	Bronze	Shade covering	T i	nen Off-White	Finials	
		allows some light shine through.	V	C-WHI: Vinyl Coated		
	CANOPY COLOR	Vertical bars are	e W	hite		
	STANDARD	exposed.				
	WHI: White	VERTICAL T	RIM.			
	PREMIUM	1/2" trim applie				
	NIC: Nickel BRA: Brass	shade exterior o				
	BLA: Black	vertical support				
	IVO: Ivory	to hide shadows	5.			
	ORB: Oil-Rubbed Bronze	2				