maratodd

FIXTURE TYPE

GABRIELLA SQUARE-DRUM FLEX CORD

www.maratodd.com

GABRIELLA

DATE	
ITEM#	MT-GABRIELLA-SQUARE-FLEX CORD
PROJECT	
COMMENTS	
PREPARED BY	



DESCRIPTION

GABRIELLA Square Pendant Light with Flex Cord Suspension Style with Optional Aircraft Cable.

SPECIFICATION FEATURES

MATERIAL / MOUNTING

Cold-rolled steel frame wire body. Matte white acrylic bottom diffuser (Optional).

SHADES

Solid cold-rolled steel construction. Material on heavy translucent white styrene with your choice of the covering's opacity.

FINISH

Standard: White (WHI)

Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed

Bronze (ORB)

ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available but may impact extended lead time and standard price.

LIGHTING

Standard socket available in multiple configurations. Works with incandescent or LED bulbs.

INSTALLATION

Easy-to-install universal swivel socket to attach to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

USAGE

Approved for interior locations only.

MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification. Pre-selected values in black may also be modified, if required.

GABRIELLA SQUARE-DRUM FLEX CORD

SERIES

GABRIELLA: Square-DRUM Pendant Light

32 x 32	12	FC	1		
SHADE TOP	SHADE HEIGHT	<u>SUSPENSION</u>	<u>SOCKET</u>	<u>BRIGHTNESS</u>	
<u>DIMENSION</u> Even numbers only in inches, minimum 6" with maximum of 84"	Numbers only in inches, minimum 4" with maximum of 40"	STYLE FC: Flex Cord Only AC: Aircraft Cable Option	Single	<u>9W</u> 800 Lumens	1,600 Lumens
32 x 32 SHADE BOTTOM DIMENSION		Note: Optional on fixtures up to 38" in diameter	Double Triple 5-Bulb	1,600 Lumens 2,400 Lumens 4,000 Lumens	3,200 Lumens 4,800 Lumens 8,000 Lumens
Even numbers only in inches, minimum 6" with maximum of 84"		Required on fixtures with diameter of 40"+		COLOR TEMPERATURE 2,700K - Warm White 3,000K – Soft White	

POWER CORD LENGTH In inches, up to 192" STANDARD PREMIUM POWER CORD STANDARD PREMIUM POWER CORD STANDARD NIC: Nickel STANDARD PREMIUM POWER CORD STANDARD STANDARD PREMIUM POWER CORD STANDARD STANDARD BLA: Black STANDARD C-BLA: Black C-WHI: White C-WHI: White PREMIUM ORB: Oil-Rubbed Bronze VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to hide shadows. LAMPSHADE COVERING COVERING STANDARD A: With Acrylic Diffuser Some Examples) Diffuser NA: Without Acrylic					A
	LENGTH In inches, up to 192" POWER CORD COLOR STANDARD C-BLA: Black	STANDARD WHI: White PREMIUM NIC: Nickel BRA: Brass BLA: Black IVO: Ivory	OPACITY OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) TRANSLUCENT: Shade covering allows some light to shine through. Vertical bars are exposed. VERTICAL TRIM: 1/2" trim applied to shade exterior over vertical support bars to	COVERING STANDARD (Some Examples) L-CRE: Linen Cream L-WHI: Linen White PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated	A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser Note: Fixture Diameters of 40"+ get Diffuser