

LUMA SHADE

FIXTURE
TYPE

DENVER

155 West 3rd St • New Richmond, WI 54017
p: 715.246.2233 f: 715.246.2243
www.maratodd.com



DENVER

DATE	
ITEM #	LS-DENVER
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

Lumashade Round Drum Pendant Light

SPECIFICATION FEATURES

CONSTRUCTION

1/4" steel wireframe, painted for optimum reflectivity.
Power source located on-board or remote in ceiling.
Cable mount suspension system (supplied).

LIGHT SOURCE

Proprietary epoxy encased light emitting diode round disc.

NO. LEDs AND LIGHT OUTPUT

8" Round Disc (87 LEDs) - 1,800 Max Lumens
16" Round Disc (192 LEDs) - 4,000 Max Lumens
24" (440 LEDs) and 32" (446) Round Disc - 9,000 Max Lumens

COLOR RENDERING INDEX

>75
MAXIMUM WATTAGE
8" Round Disc - 18.2W
16" Round Disc - 40W
24" and 32" Rounds Disc - 90W

ENVIRONMENT

Dry or Damp
AMBIENT TEMPERATURE

CONTROLLER

MW UL Approved (>20W, >40W or >90W depending on LED disc selected).

CERTIFICATIONS

CE, RoHS, FCC, IP-67

INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.
Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

USAGE

Approved for interior locations only.

MODIFICATIONS

Lumashade's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all **blue highlighted** areas for complete specification. Preselected values may also be modified, if required.

DENVER

SERIES

DENVER: Lumashade Round
Drum Pendant Light

30

13

AC

SHADE
DIAMETER

IN INCHES

6, 8, 10, 12, 14, 16, 18, 20,
22, 24, 26, 28, 30, 32, 34,
36, 38, 40, 42, 44, 46, 48,
50, 52, 54, 56, 58, 60, 62

SHADE
HEIGHT

IN INCHES

6, 8, 10, 12, 14, 16, 18, 20,
22, 24, 26, 28, 30, 32, 34,
36, 38, 40, 42, 44, 46, 48,
50, 52, 54, 56, 58, 60, 62

SUSPENSION
STYLE

SRS: Swivel Rigid Stem

FS: Fixed Stem

FC: Flex Cord

AC: Aircraft Cable
with Flex Cord

CANOPY
COLOR

STANDARD

WHI: White

PREMIUM:

NIC: Nickel

BRA: Brass

BLA: Black

IVO: Ivory

ORB: Oil-Rubbed Bronze

A

24

POWER
CORD
COLOR

STANDARD

C-BLA: Black

C-WHI: White

LAMP SHADE
OPACITY

OPAQUE:

Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade)

TRANSLUCENT:

Shade covering allows some light to shine through.

LAMP SHADE
COVERING

STANDARD

(Some Examples)

L-CRE: Linen Cream

L-WHI: Linen White

PREMIUM

(Some Examples)

DL-OFF: Designer

Linen Off-White

VC-WHI: Vinyl

Coated White

ACRYLIC
DIFFUSER

A: With Acrylic Diffuser

FBD: With Fabric Diffuser

NA: Without Acrylic Diffuser

LUMA DISC
SIZE

8: 8" Luma Disc

16: 16" Luma Disc

24: 24" Luma Disc

32: 32" Luma Disc

POWER
CORD
LENGTH

IN FEET

4, 8, 12, 16

DIMMING

N: No Dimming

0-10V: 0-10V
PWM Dimming

RC: Remote
Control Dimming

COLOR
TEMPERATURE

3K: Warm White

4K: Neutral White