

# LUMA SHADE

FIXTURE  
TYPE

CHARLOTTE

155 West 3rd St • New Richmond, WI 54017  
p: 715.246.2233 f: 715.246.2243  
www.maratodd.com



## CHARLOTTE

DATE	
ITEM #	LS-CHARLOTTE
PROJECT	
COMMENTS	
PREPARED BY	

## DESCRIPTION

Lumashade Rectangle Pendant Light

## SPECIFICATION FEATURES

### CONSTRUCTION

1/4" steel wireframe, painted for optimum reflectivity.  
Power source located on-board or remote in ceiling.  
Cable mount suspension system (supplied).

### LIGHT SOURCE

Proprietary epoxy encased light emitting diode round disc.

### NO. LEDs AND LIGHT OUTPUT

8" Round Disc (87 LEDs) - 1,800 Max Lumens  
16" Round Disc (192 LEDs) - 4,000 Max Lumens  
24" (440 LEDs) and 32" (446) Round Disc - 9,000 Max Lumens

### COLOR RENDERING INDEX

>75  
MAXIMUM WATTAGE  
8" Round Disc - 18.2W  
16" Round Disc - 40W  
24" and 32" Rounds Disc - 90W

### ENVIRONMENT

Dry or Damp  
AMBIENT TEMPERATURE  
22°F - 122°F

### CONTROLLER

MW UL Approved (>20W, >40W or >90W depending on LED disc selected).

### CERTIFICATIONS

CE, RoHS, FCC, IP-67

### INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.  
Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Lumashade's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

# ORDERING INFORMATION

Please fill in all **blue highlighted** areas for complete specification. Preselected values may also be modified, if required.

## CHARLOTTE

SERIES

CHARLOTTE: Lumashade  
Rectangle Pendant Light

24 X 42		24 X 42		AC	
<u>TOP WIDTH X HEIGHT</u>		<u>BOTTOM WIDTH X HEIGHT</u>		<u>SUSPENSION STYLE</u>	
20				<b>SRS:</b> Swivel Rigid Stem <b>FS:</b> Fixed Stem <b>FC:</b> Flex Cord <b>AC:</b> Aircraft Cable with Flex Cord	
<u>SHADE HEIGHT</u>				<u>CANOPY COLOR</u>	
<b>BOTH IN INCHES</b> 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48				<b>STANDARD</b> <b>WHI:</b> White <b>PREMIUM:</b> <b>NIC:</b> Nickel <b>BRA:</b> Brass <b>BLA:</b> Black <b>IVO:</b> Ivory <b>ORB:</b> Oil-Rubbed Bronze	

			A		24		
<u>POWER CORD COLOR</u>		<u>LAMPSHADE OPACITY</u>		<u>LAMPSHADE COVERING</u>		<u>ACRYLIC DIFFUSER</u>	
<b>STANDARD</b> <b>C-BLA:</b> Black <b>C-WHI:</b> White		<b>OPAQUE:</b> Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) <b>TRANSLUCENT:</b> Shade covering allows some light to shine through.		<b>STANDARD (Some Examples)</b> <b>L-CRE:</b> Linen Cream <b>L-WHI:</b> Linen White <b>PREMIUM (Some Examples)</b> <b>DL-OFF:</b> Designer Linen Off-White <b>VC-WHI:</b> Vinyl Coated White		<b>8:</b> 8" Luma Disc <b>16:</b> 16" Luma Disc <b>24:</b> 24" Luma Disc <b>32:</b> 32" Luma Disc	
<u>POWER CORD LENGTH</u>				<u>DIMMING</u>		<u>COLOR TEMPERATURE</u>	
<b>IN FEET</b> 4, 8, 12, 16				<b>N:</b> No Dimming <b>0-10V:</b> 0-10V PWM Dimming <b>RC:</b> Remote Control Dimming		<b>3K:</b> Warm White <b>4K:</b> Neutral White	