

FIXTURE TYPE

TAMPA

155 West 3rd St • New Richmond, WI 54017 p: 715.246.2233 f: 715.246.2243 www.maratodd.com



TAMPA

DATE	
ITEM #	LS-TAMPA
PROJECT	
COMMENTS	
PREPARED BY	

DESCRIPTION

Lumashade Round Drum Pendant Light

SPECIFICATION FEATURES

CONSTRUCTION

1/4" steel wireframe, painted for optimum reflectivity.

Power source located on-board or remote in ceiling.

Cable mount suspension system (supplied).

LIGHT SOURCE

Proprietary epoxy encased light emmitting diode round disc.

NO. LEDS AND LIGHT OUTPUT

8" Round Disc (87 LEDs) - 1,800 Max Lumens

16" Round Disc (192 LEDs) - 4,000

Max Lumens

24" (440 LEDs) and 32" (446)

Round Disc - 9,000 Max Lumens

COLOR RENDERING INDEX

>75

MAXIMUM WATTAGE

8" Round Disc - 18.2W 16" Round Disc - 40W 24" and 32" Rounds Disc - 90W ENVIRONMENT

Dry or Damp

AMBIENT TEMPERATURE

22°F - 122°F

CONTROLLER

MW UL Approved (>20W, >40W or >90W depending on LED disc selected).

CERTIFICATIONS

CE, RoHS, FCC, IP-67

INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.
Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

USAGE

Approved for interior locations only. MODIFICATIONS

Lumashade's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

ORDERING INFORMATION

Please fill in all blue highlighted areas for complete specification. Preselected values may also be modified, if required.

TAMPA

SERIES

TAMPA: Lumashade Round Drum

Pendant Light

4 8	2 4	A C	
<u>SHADE</u> <u>DIAMETER</u>	SHADE HEIGHT	<u>SUSPENSION</u> <u>STYLE</u>	<u>CANOPY</u> <u>COLOR</u>
IN INCHES	IN INCHES	SRS: Swivel Rigid Stem	STANDARD
6, 8, 10, 12, 14, 16, 18, 20,	6, 8, 10, 12, 14, 16, 18, 20,	FS: Fixed Stem	WHI: White
22, 24, 26, 28, 30, 32, 34,	22, 24, 26, 28, 30, 32, 34,	FC: Flex Cord	PREMIUM:
36, 38, 40, 42, 44, 46, 48,	36, 38, 40, 42, 44, 46, 48,	AC: Aircraft Cable	NIC: Nickel
50, 52, 54, 56, 58, 60, 62	50, 52, 54, 56, 58, 60, 62	with Flex Cord	BRA: Brass
			BLA: Black
			IVO: Ivory
			ORB: Oil-Rubbed Bronze

			Α	8
POWER CORD COLOR STANDARD C-BLA: Black C-WHI: White	LAMPSHADE OPACITY OPAQUE: Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) TRANSLUCENT:	STANDARD (Some Examples) L-CRE: Linen Cream L-WHI: Linen White PREMIUM (Some Examples) DL-OFF: Designer Linen Off-White VC-WHI: Vinyl Coated White	ACRYLIC DIFFUSER A: With Acrylic Diffuser FBD: With Fabric Diffuser NA: Without Acrylic Diffuser	LUMA DISC SIZE 8: 8" Luma Disc 16: 16" Luma Disc 24: 24" Luma Disc 32: 32" Luma Disc
POWER CORD LENGTH IN FEET 4, 8, 12, 16	Shade covering allows some light to shine through.		DIMMING N: No Dimming 0-10V: 0-10V PWM Dimming RC: Remote Control Dimming	COLOR TEMPERATURE 3K : Warm White 4K : Neutral White