



## F E D O R

DATE	
ITEM #	MT-FEDOR
PROJECT	
COMMENTS	
PREPARED BY	

## D E S C R I P T I O N

Round Drum Pendant Light

## S P E C I F I C A T I O N F E A T U R E S

### MATERIAL / MOUNTING

Cold-rolled steel frame wire body.  
Matte white acrylic bottom diffuser (Optional).

### SHADES

Solid cold-rolled steel construction.  
Material on heavy translucent white styrene with your choice of the coverings opacity.

### FINISH

Standard: White (WHI)  
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

### INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

## ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.  
Pre-selected values may also be modified, if required.

## FEDOR

### SERIES

FEDOR: Round Drum  
Pendant Light

7 2	1 0	AC - HK			
<u>SHADE</u> <u>DIAMETER</u>	<u>SHADE</u> <u>HEIGHT</u>	<u>SUSPENSION</u> <u>STYLE</u>	<u>CANOPY</u> <u>COLOR</u>	<u>POWER</u> <u>CORD</u> <u>COLOR</u>	<u>POWER CORD</u> <u>LENGTH</u>
IN INCHES	IN INCHES	SRS: Swivel Rigid	STANDARD	STANDARD	IN FEET
6, 8, 10, 12, 14, 16, 18,	6, 8, 10, 12, 14, 16, 18,	Stem	WHI: White	C-BLA: Black	4, 8, 12, 16
20, 22, 24, 26, 28, 30,	20, 22, 24, 26, 28, 30,	FS: Fixed Stem	PREMIUM:	C-WHI: White	
32, 34, 36, 38, 40, 42,	32, 34, 36, 38, 40, 42,	AC-HK: Aircraft	NIC: Nickel		
44, 46, 48, 50, 52, 54,	44, 46, 48, 50, 52, 54,	Cable with Hooks	BRA: Brass		
56, 58, 60, 62, 64, 68,	56, 58, 60, 62, 64, 68,	AC-TB: Aircraft Cable	BLA: Black		
70, 72, 74, 76, 78, 80	70, 72, 74, 76, 78, 80	with Tabs	IVO: Ivory		
		AC: Aircraft Cable	ORB: Oil-Rubbed		
		with	Bronze		
		Flex Cord			

		N / A	5	
<u>LAMP SHADE</u> <u>OPACITY</u>	<u>LAMP SHADE</u> <u>COVERING</u>	<u>ACRYLIC</u> <u>DIFFUSER</u>	<u>LAMPING</u>	<u>BULBS</u>
OPAQUE:	STANDARD	A: With floating	Specify Number of	Number of Bulbs
Features an interior	(Some Examples)	Acrylic Diffuser	Light Sockets	Depends on Socket
light-blocking layer to	L-CRE: Linen Cream	(attached with	1, 2, 3, 5	9W2700:
make shade opaque. (No	L-WHI: Linen White	diffuser risers )		800 Lumens 2,700K
light passes through the	PREMIUM			15W2700:
sides of the shade)	(Some Examples)	FBD: With Fabric		1,600 Lumens 2,700K
TRANSLUCENT:	DL-OFF: Designer Linen	Diffuser		NA: No Bulbs
Shade covering allows	Off-White	NA: Without		
some light to shine	VC-WHI: Vinyl Coated	Acrylic Diffuser		
through. Vertical bars	White			
are exposed.				
VERTICAL TRIM:				
1/2" trim applied to shade				
exterior over				
vertical support bars to				
hide shadows.				