



## GERALD

|             |           |
|-------------|-----------|
| DATE        |           |
| ITEM #      | MT-GERALD |
| PROJECT     |           |
| COMMENTS    |           |
| PREPARED BY |           |

## DESCRIPTION

Round Drum Pendant Light

## SPECIFICATION FEATURES

### MATERIAL / MOUNTING

Cold-rolled steel frame wire body.  
Matte white acrylic bottom diffuser (Optional).

### SHADES

Solid cold-rolled steel construction.  
Material on heavy translucent white styrene with your choice of the coverings opacity.

### FINISH

Standard: White (WHI)  
Premium: Nickel (NIC), Brass (BRA), Black (BLA), Ivory (IVO), Oil-Rubbed Bronze (ORB)

### ACRYLIC DIFFUSER

Our standard acrylic is 7328 White with a thickness of 0.118. Custom colors are available, but may impact extended lead time and standard price.

### LIGHTING

Single Socket. Works with incandescent or LED bulbs.

### INSTALLATION

Easy-to-install. Attaches to standard 4" junction box. 120V power.

Cleaning Recommendation: Use a soft cloth brush or a vacuum brush to dust the outside of the lamp shade and a clean soft white flannel cloth for the inside of the lampshade.

### OPTIONS

Contact factory for NFP701 Fire Resistant or Stain Guard Fabric coating.

### USAGE

Approved for interior locations only.

### MODIFICATIONS

Maratodd's skilled craftspeople, with their depth of experience, offer the designer the flexibility to modify standard luminaries for project-specific solutions. Contact the factory regarding scale options, unique finishes, mounting, additional materials/colors or decorative detailing.

# ORDERING INFORMATION

Please fill in all **gold highlighted** areas for complete specification.  
Pre-selected values may also be modified, if required.

## GERALD

### SERIES

GERALD: Round Drum  
Pendant Light

16

10

FC

| <u>SHADE DIAMETER</u>  | <u>SHADE HEIGHT</u>   | <u>SUSPENSION STYLE</u>   | <u>CANOPY COLOR</u>  | <u>CORD COLOR</u>            |
|--|---|---|--|------------------------------|
| IN INCHES  | IN INCHES   | SRS: Swivel Rigid Stem  | STANDARD   | STANDARD                     |
| 6, 8, 10, 12, 14, 16,<br>18, 20, 22, 24, 26,<br>28, 30, 32, 34, 36 | 6, 8, 10, 12, 14, 16,<br>18, 20, 22, 24, 26,<br>28, 30, 32, 34, 36,<br>38, 40, 42, 44, 46,<br>48, 50, 52, 54, 56,<br>58, 60 | FS: Fixed Stem<br>FC: Flex Cord<br>AC: Aircraft Cable with<br>Flex Cord | WHI: White<br>PREMIUM<br>NIC: Nickel<br>BRA: Brass<br>BLA: Black<br>IVO: Ivory<br>ORB: Oil-Rubbed Bronze | C-WHT: WHITE<br>C-BLK: BLACK |
|  |   |   |  | <u>CORD LENGTH</u>           |
|  |   |   |  | 4FT. 12FT.<br>8FT. 16FT.     |

A

3

| <u>LAMP SHADE OPACITY</u>   | <u>LAMP SHADE COVERING</u>   | <u>ACRYLIC DIFFUSER</u>                               | <u>LAMPING</u>                                | <u>BULBS</u>   |
|---|--|---|---|--|
| OPAQUE:<br>Features an interior light-blocking layer to make shade opaque. (No light passes through the sides of the shade) | STANDARD<br>(Some Examples)<br>L-CRE: Linen Cream<br>L-WHI: Linen White                      | A: With Acrylic Diffuser<br>FBD: With Fabric Diffuser | Specify Number of Light Sockets<br>1, 2, 3, 5 | Number of Bulbs Depends on Socket<br>9W2700:<br>800 Lumens 2,700K<br>15W2700:<br>1,600 Lumens 2,700K<br>NA: No Bulbs |
| TRANSLUCENT:<br>Shade covering allows some light to shine through.  | PREMIUM<br>(Some Examples)<br>DL-OFF: Designer Linen Off-White<br>VC-WHI: Vinyl Coated White | NA: Without Acrylic Diffuser                          |   |  |
| VERTICAL TRIM:<br>1/2" trim applied to shade exterior over vertical support bars to hide shadows.                           |  |   |   |  |